



Gold Fields Ghana Limited

The use of RTK GPS in Open Pit Survey – A Case study at Gold Fields Ghana Limited, Tarkwa, Ghana.



by

MENSAH Francis, MPhil student &
Chief Surveyor, GGL
DUNCAN Edward Eric, MSc
(Glasgow) BSc (Kumasi) Lecturer



Gold Fields Ghana Limited

Introduction

- GPS is being used for Planimetric controls, detailing as well as a wide variety of engineering applications.
- Goldfields Ghana Limited (GGL) currently operates 10 active mine pits with pit locations being at a maximum distance of 6km apart. GGL management took the bold decision of purchasing some GPS equipment to help facilitate the surveying process and enhancing the map-making process of the company.



Gold Fields Ghana Limited

History of the Mine

- Mining in the Tarkwa area started as far back as 1800. Around 1877, Skarchley visited Tarkwa and there were about 600 natives engaged in gold production by digging pits to depth of about 24 m or more.
- The Tarkwa mines started around 1878 by a French company under the management of Bonnet until the mine closed down in early 19 century.
- In line with the Ghana Government economic recovery programme, a memorandum of agreement of incorporating the project development was signed on the 26th May 1993, in which GGL acquired 85% shares and took over the operations of the mine on 1st July 1993.



Gold Fields Ghana Limited

Location, Climate and Topography

- The project area falls within the equatorial climatic zone.
- The topography of the lease area comprises ragged ridges with peaks of 335 m above mean sea level in some areas, interspersed by undulating valley bottoms.



Gold Fields Ghana Limited

GPS Survey at Gold Fields Ghana Limited


- RTK survey was introduced to GGL in December 2004 to augment the fleet of Sokkia Total Stations being used on the mine.
- The RTK survey system at GGL comprises of 1 R5700 Trimble unit as the main base, 1 R 5800 mobile base, and 5 R 5800 Trimble receivers.



Gold Fields Ghana Limited

Cont'

- Figure 2 shows the main base station set up at the survey office with the antenna on the roof of the survey office. A calibration survey was performed on 8 known coordinates to establish the known point for the base.



Calibration Results

From To	Min. no of satellites	RMS(m)	Calibration Survey			PDOP(m)
			Baseline distance(m)	Horizontal precision(m)	Vertical precision(m)	
Thana-PTSM	7	0.005	3481.382	0.010	0.016	1.365
Thana-PTSM	7	0.004	2418.006	0.010	0.017	1.451
Thana-PSM	4	0.004	1835.020	0.007	0.017	2.094
Thana-TERIM	7	0.003	2917.489	0.006	0.013	1.888
Thana-GFD13M	10	0.006	5196.384	0.010	0.017	1.524
Thana-AKESM	7	0.003	1468.394	0.006	0.011	1.393
Thana-AKESM	10	0.005	1957.397	0.007	0.012	1.124
Thana-KOTSM	10	0.006	4412.582	0.007	0.012	1.135

Calibration Results

Weighted Ambiguity Vector Estimate (WAVE) provided statistics to evaluate the quality of a baseline solution. The statistics in table 2 are the default values indicating good baselines.

Table 2 Default values for good Baselines

Parameters	Default Values
Reference variance	=1
Ratio	>1.5
Root Mean Square (RMS)	<15mm
PDOP	<7
Residual Plots	±15mm

- Cont'**
- From the results above, the RMS values were all within the acceptable limit of <15mm, the PDOP were within acceptable limits of 3 as used in the Trimble Survey Controller. A horizontal precision of 8mm and vertical precision of 14mm were achieved.
 - The known coordinate of the main base station on WGS-84, Ghana National Grid and GGL Grid was generated and tabulated in table 3.

Cont'

Table 3 Base Station ground Coordinates in 3 grid systems

Base Station	Latitude	Longitude	Ellipsoidal height	Remarks
WGS-84	5-19-34.0907N	2-01-26.2801W	125.069m	Universal
Ghana Grid	72686.740	160812.173	125.069m	National
GGL grid	11059.882	8674.491	125.069m	Local

- Comparison of RTK survey and Total Station survey**
- In other to ascertain the accuracy of the RTK operations, a comparison between conventional survey using Total Station measurement and RTK GPS measurement was performed and the outcome of the survey were as follows:

Table 4: RTK and Total station Survey Analysis




RTK GPS SURVEY			TOTAL STATION SURVEY			
EASTING	NORTHING	ELEVATION	EASTING	NORTHING	ELEVATION	CODE
8048.774	10831.035	112.315	8048.767	10830.997	112.374	RP1
8465.867	9587.101	183.872	8465.851	9587.116	183.662	AK22
8925.873	8612.288	181.154	8925.849	8612.261	181.772	AK23
9279.892	8162.984	98.704	9279.893	8162.976	98.689	MT13
10248.179	8729.079	148.386	10248.171	8729.063	148.028	GT5
10576.892	8340.838	154.842	10576.873	8340.824	154.100	GT3
10467.634	8746.116	179.240	10467.640	8746.094	179.273	RP11
10484.916	8572.653	160.184	10484.925	8572.650	160.192	GT4
10486.752	8721.846	160.358	10486.734	8721.871	160.316	GT3
10472.040	8851.035	147.591	10472.048	8851.008	147.468	GT2
10465.591	8994.116	134.848	10465.577	8994.091	134.819	GT1

DEVIATION			CODE	MISCLOSURE	VECTOR(m)	
dx	dy	dz				
0.007	0.038	-0.063	RP1	0.039	0.000	
0.030	-0.027	0.250	AK22	0.031	0.000	
0.021	-0.033	-0.027	AK23	0.038	0.000	
0.000	0.008	-0.050	MT13	0.008	0.001	
0.048	0.014	-0.042	GT6	0.050	0.000	
0.024	0.012	-0.018	GT5	0.027	0.000	
0.014	0.030	-0.075	RP11	0.030	0.000	
0.002	0.053	-0.006	GT4	0.089	0.001	
0.018	-0.003	-0.042	GT3	0.018	0.000	
0.008	0.027	-0.023	GT2	0.028	0.000	
0.014	0.025	0.008	GT1	0.029	0.000	
			MEAN	0.033	SO	0.001

Cont'

- The results between the two techniques compared very well with the distance closures ranging from 8mm to 59mm, with an average closure of 33mm and a standard deviation of 1mm.

- The Usage**
- Currently, RTK GPS is being used at GGL for the following surveys:
 - Road survey
 - Topographical survey (Pit floor pick ups,)
 - Stakeout survey (grade control, mine design pegs, blast pattern layout)
 - Stockpile survey





-
- THANK YOU
 - Question Time