

# Model of Fiber-Optic Torsion Gravimeter Based on Tilted FBG for Continuous Gravity Field Monitoring

Artem Mareev, Aleksandr Makeev and Valentin Yangalishev (Russia)

**Key words:** Low cost technology; Reference systems; Remote sensing; gravimetry; torsion gravimeter; IHRS; distributed sensing

## SUMMARY

One of the key challenges in geodesy is the lack of a continuously operating, high-precision gravimetric infrastructure to support the International Height Reference System (IHRS). Relative gravimeters, while sensitive to  $\sim 0.1 \mu\text{Gal}$ , are expensive, require manual operation, and are unsuitable for long-term autonomous monitoring. The paper presents a novel approach to gravity sensing using fiber-optic technology, specifically tilted fiber Bragg gratings (TFBGs), integrated into a differential torsion-lever gravimeter configuration.

The proposed model of sensing element replaces conventional displacement transducers with optical fibers that simultaneously serve as elastic torsion suspensions and strain-sensitive waveguides. Two standard SMF-28 fibers, each inscribed with five TFBG segments, are mounted symmetrically on opposite sides of a lever arm carrying a proof mass. When gravity changes, one fiber twists while the other untwists, enabling common-mode rejection of thermal and environmental noise while doubling the useful signal. Using an industrial interrogator with 1 pm wavelength resolution and a TFBG torsional sensitivity of 0.3 nm/(rad/m), the system can achieve a theoretical resolution of 20  $\mu\text{Gal}$  at a signal-to-noise ratio greater than 3.

A key advantage of the design is its use of torsional deformation of the elastic system—the dominant response mechanism in high-sensitivity gravimeters—rather than axial strain. This approach overcomes the limited sensitivity of standard fiber Bragg gratings to linear strain ( $\sim 1.2 \text{ pm}/\mu\epsilon$ ) and instead exploits the enhanced torsional sensitivity of tilted fiber Bragg gratings (TFBGs). The all-silica construction ensures low thermal drift, while the differential readout scheme enables effective compensation for temperature-induced disturbances.

Furthermore, the architecture is inherently scalable: multiple sensors can be multiplexed along a

---

Model of Fiber-Optic Torsion Gravimeter Based on Tilted FBG for Continuous Gravity Field Monitoring (13976)  
Artem Mareev, Aleksandr Makeev and Valentin Yangalishev (Russia)

FIG Congress 2026  
The Future We Want - The SDGs and Beyond  
Cape Town, South Africa, 24–29 May 2026

single fiber, and interrogators can be linked via dedicated optical lines to form regional or even continental gravimetric networks. Modeling a 7,000 km chain (Moscow–Vladivostok) shows that with 70 such TFBG-gravimeters and 100 s signal averaging, accumulated error can be reduced to 0.02 mGal, enabling real-time monitoring of gravity changes with microgal-level precision over intercontinental distances.

This approach enables fully automated, remotely operated gravimetric networks compatible with existing telecom infrastructure, offering a cost-effective pathway toward a dynamic, fiber-optic-based IHRs.

---

Model of Fiber-Optic Torsion Gravimeter Based on Tilted FBG for Continuous Gravity Field Monitoring (13976)  
Artem Mareev, Aleksandr Makeev and Valentin Yangalishev (Russia)

FIG Congress 2026  
The Future We Want - The SDGs and Beyond  
Cape Town, South Africa, 24–29 May 2026